12.6 External Storage or Memory-Local FFTs

Sometime in your life, you might have to compute the Fourier transform of a *really large* data set, larger than the size of your computer's physical memory. In such a case, the data will be stored on some external medium, such as magnetic or optical tape or disk. Needed is an algorithm that makes some manageable number of sequential passes through the external data, processing it on the fly and outputting intermediate results to other external media, which can be read on subsequent passes.

In fact, an algorithm of just this description was developed by Singleton [1] very soon after the discovery of the FFT. The algorithm requires four sequential storage devices, each capable of holding half of the input data. The first half of the input data is initially on one device, the second half on another.

Singleton's algorithm is based on the observation that it is possible to bit-reverse 2^M values by the following sequence of operations: On the first pass, values are read alternately from the two input devices, and written to a single output device (until it holds half the data), and then to the other output device. On the second pass, the output devices become input devices, and vice versa. Now, we copy two values from the first device, then two values from the second, writing them (as before) first to fill one output device, then to fill a second. Subsequent passes read 4, 8, etc., input values at a time. After completion of pass M-1, the data are in bit-reverse order.

Singleton's next observation is that it is possible to alternate the passes of essentially this bit-reversal technique with passes that implement one stage of the Danielson-Lanczos combination formula (12.2.3). The scheme, roughly, is this: One starts as before with half the input data on one device, half on another. In the first pass, one complex value is read from each input device. Two combinations are formed, and one is written to each of two output devices. After this "computing" pass, the devices are rewound, and a "permutation" pass is performed, where groups of values are read from the first input device and alternately written to the first and second output devices; when the first input device is exhausted, the second is similarly processed. This sequence of computing and permutation passes is repeated M-K-1 times, where 2^K is the size of internal buffer available to the program. The second phase of the computation consists of a final K computation passes. What distinguishes the second phase from the first is that, now, the permutations are local enough to do in place during the computation. There are thus no separate permutation passes in the second phase. In all, there are 2M-K-2 passes through the data.

Here is an implementation of Singleton's algorithm, based on [1]:

```
SUBROUTINE fourfs(iunit,nn,ndim,isign)
INTEGER ndim,nn(ndim),isign,iunit(4),KBF
PARAMETER (KBF=128)
```

C USES fourew

One- or multi-dimensional Fourier transform of a large data set stored on external media. On input, ndim is the number of dimensions, and $\mathtt{nn}(1:\mathtt{ndim})$ contains the lengths of each dimension (number of complex values), which must be powers of two. $\mathtt{iunit}(1:4)$ contains the unit numbers of 4 sequential files, each large enough to hold half of the data. The four units must be opened for FORTRAN unformatted access. The input data must be in FORTRAN normal order, with its first half stored on unit $\mathtt{iunit}(1)$, its second half on $\mathtt{iunit}(2)$, in unformatted form, with KBF real numbers per record. \mathtt{isign} should be set to 1 for the Fourier transform, to -1 for its inverse. On output, values in the array \mathtt{iunit} may have been permuted; the first half of the result is stored on $\mathtt{iunit}(3)$, the second half on $\mathtt{iunit}(4)$. N.B.: For $\mathtt{ndim} > 1$, the output is stored by rows, i.e., not in FORTRAN normal order; in other words, the output is the transpose of that which would have been produced by routine fourn.

```
INTEGER j,j12,jk,k,kk,n,mm,kc,kd,ks,kr,nr,ns,nv,jx,
    mate(4),na,nb,nc,nd
REAL tempr,tempi,afa(KBF),afb(KBF),afc(KBF)
DOUBLE PRECISION wr,wi,wpr,wpi,wtemp,theta
SAVE mate
DATA mate /2,1,4,3/
```

```
n=1
    do 11 j=1,ndim
       n=n*nn(j)
       if (nn(j).le.1)
            pause 'invalid dimension or wrong ndim in fourfs'
    enddo 11
   nv=ndim
    jk=nn(nv)
    mm=n
   ns=n/KBF
   nr=ns/2
   kc=0
   kd=KBF/2
   ks=n
    call fourew(iunit,na,nb,nc,nd)
      The first phase of the transform starts here.
                                 Start of the computing pass.
       theta=3.141592653589793d0/(isign*n/mm)
       wpr=-2.d0*sin(0.5d0*theta)**2
       wpi=sin(theta)
       wr=1.d0
       wi=0.d0
       mm=mm/2
       do 13 j12=1,2
           kr=0
2
            continue
               read (iunit(na)) (afa(jx),jx=1,KBF)
               read (iunit(nb)) (afb(jx),jx=1,KBF)
               do 12 j=1,KBF,2
                   tempr=sngl(wr)*afb(j)-sngl(wi)*afb(j+1)
                   tempi=sngl(wi)*afb(j)+sngl(wr)*afb(j+1)
                   afb(j)=afa(j)-tempr
                   afa(j)=afa(j)+tempr
                   afb(j+1)=afa(j+1)-tempi
                   afa(j+1)=afa(j+1)+tempi
               enddo 12
               kc=kc+kd
               if (kc.eq.mm) then
                   kc=0
                   wtemp=wr
                   wr=wr*wpr-wi*wpi+wr
                   wi=wi*wpr+wtemp*wpi+wi
               write (iunit(nc)) (afa(jx),jx=1,KBF)
               write (iunit(nd)) (afb(jx),jx=1,KBF)
           kr=kr+1
            if (kr.lt.nr) goto 2
            if(j12.eq.1.and.ks.ne.n.and.ks.eq.KBF) then
               na=mate(na)
               nb=na
            endif
            if (nr.eq.0) goto 3
       enddo 13
3
       call fourew(iunit,na,nb,nc,nd)
                                               Start of the permutation pass.
       jk=jk/2
        if (jk.eq.1) then
           mm=n
           nv=nv-1
           jk=nn(nv)
       goto 4
       endif
       ks=ks/2
       if (ks.gt.KBF) then
            do 16 j12=1,2
```

```
do 15 kr=1,ns,ks/KBF
                   do 14 k=1,ks,KBF
                       read (iunit(na)) (afa(jx), jx=1, KBF)
                       write (iunit(nc)) (afa(jx),jx=1,KBF)
                   enddo 14
                   nc=mate(nc)
               enddo 15
               na=mate(na)
           call fourew(iunit,na,nb,nc,nd)
           goto 1
       else if (ks.eq.KBF) then
           nb=na
           goto 1
       endif
   continue
   j=1
     The second phase of the transform starts here. Now, the remaining permutations are suffi-
     ciently local to be done in place.
   continue
       theta=3.141592653589793d0/(isign*n/mm)
       wpr=-2.d0*sin(0.5d0*theta)**2
       wpi=sin(theta)
       wr=1.d0
       wi=0.d0
       mm=mm/2
       ks=kd
       kd=kd/2
       do 18 j12=1,2
           do 17 kr=1.ns
               read (iunit(na)) (afc(jx),jx=1,KBF)
               k=ks+1
6
               continue
                   tempr=sngl(wr)*afc(kk+ks)-sngl(wi)*afc(kk+ks+1)
                   tempi=sngl(wi)*afc(kk+ks)+sngl(wr)*afc(kk+ks+1)
                   afa(j)=afc(kk)+tempr
                   afb(j)=afc(kk)-tempr
                   afa(j+1)=afc(kk+1)+tempi
                   afb(j+1)=afc(kk+1)-tempi
                   j=j+2
                   kk=kk+2
               if (kk.lt.k) goto 6
               kc=kc+kd
               if (kc.eq.mm) then
                   kc=0
                   wtemp=wr
                   wr=wr*wpr-wi*wpi+wr
                   wi=wi*wpr+wtemp*wpi+wi
               endif
               kk=kk+ks
               if (kk.le.KBF) then
                   k=kk+ks
                   goto 6
               endif
               if (j.gt.KBF) then
                   write (iunit(nc)) (afa(jx), jx=1,KBF)
                   write (iunit(nd)) (afb(jx),jx=1,KBF)
                   j=1
               endif
           enddo 17
           na=mate(na)
```

call fourew(iunit,na,nb,nc,nd)

```
jk=jk/2
if (jk.gt.1) goto 5
mm=n
if (nv.gt.1) then
   nv=nv-1
    jk=nn(nv)
   if (jk.eq.1) goto 7
    goto 5
return
END
SUBROUTINE fourew(iunit,na,nb,nc,nd)
INTEGER na,nb,nc,nd,iunit(4),ii
   Utility used by fourfs. Rewinds and renumbers the four files.
do 11 ii=1,4
   rewind(unit=iunit(ii))
enddo 11
ii=iunit(2)
iunit(2)=iunit(4)
iunit(4)=ii
ii=iunit(1)
iunit(1)=iunit(3)
iunit(3)=ii
na=3
nb=4
nc=1
nd=2
return
F.ND
```

For one-dimensional data, Singleton's algorithm produces output in exactly the same order as a standard FFT (e.g., four1). For multidimensional data, the output is the *transpose* of the conventional arrangement (e.g., the output of fourn). This peculiarity, which is intrinsic to the method, is generally only a minor inconvenience. For convolutions, one simply computes the component-by-component product of two transforms in their nonstandard arrangement, and then does an inverse transform on the result. Note that, if the lengths of the different dimensions are not all the same, then you must reverse the order of the values in nn(1:ndim) (thus giving the transpose dimensions) before performing the inverse transform. Note also that, just like fourn, performing a transform and then an inverse results in multiplying the original data by the product of the lengths of all dimensions.

We leave it as an exercise for the reader to figure out how to reorder fourfs's output into normal order, taking additional passes through the externally stored data. We doubt that such reordering is ever really needed.

You will likely want to modify fourfs to fit your particular application. For example, as written, KBF $\equiv 2^K$ plays the dual role of being the size of the internal buffers, and the record size of the unformatted reads and writes. The latter role limits its size to that allowed by your machine's I/O facility. It is a simple matter to perform multiple reads for a much larger KBF, thus reducing the number of passes by a few.

Another modification of fourfs would be for the case where your virtual memory machine has sufficient address space, but not sufficient physical memory, to do an efficient FFT by the conventional algorithm (whose memory references are extremely nonlocal). In that case, you will need to replace the reads, writes, and rewinds by mappings of the arrays afa, afb, and afc into your address space. In other words, these arrays are replaced by references to a single data array, with offsets that get modified wherever fourfs performs an I/O operation. The resulting algorithm will have its memory references local within blocks of size KBF. Execution speed is thereby sometimes increased enormously, albeit at the cost of requiring twice as much virtual memory as an in-place FFT.

CITED REFERENCES AND FURTHER READING:

Singleton, R.C. 1967, *IEEE Transactions on Audio and Electroacoustics*, vol. AU-15, pp. 91–97. [1]

Oppenheim, A.V., and Schafer, R.W. 1989, *Discrete-Time Signal Processing* (Englewood Cliffs, NJ: Prentice-Hall), Chapter 9.